



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
3	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	±Z
6	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	±Z	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
5	Button	POM	UL94HB-
4	Spring	Stainless steel	/
3	Pin header	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准 / IEC Standard:	/	/	/
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	450/17	/
工频耐压/Withstanding Voltage(V/1Min)	/	AC2500	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.0/N=01~24P		
引线长度/Stripping length(mm)	5~6		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Li GL 2020.06.10
CHKD:	MaEK 2020.06.10
DFT:	WangW 2020.06.10
NAME:	DG243-5.0-XXP-1Y-00A(H)
DRAWING NO.:	DG243-5.0-C01
TYPE:	CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DFT	DATE

SIZE: A4	SCALE: 2:1
TYPE: CUSTOMER DRAWING	SCALE: 2:1
REV	TO
1/1	1/1

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD