## LEMLUX

## **LED strip COB WHITE**



- High density, yet efficient LED strip which can be used for various applications (e.g. for furniture, architectural, accent lighting, etc.).
- High color rendering index CRI>90.
- Spotless light even illumination even with transparent LED profile cover.
- IP65 level of water ingress protection, high quality silicone layer
- Reel-to-Reel technology solderless segments up to 30m
- Easy installation (e.g. reliable double-sided adhesive tape).
- 5 years warranty

## **TECHNICAL DATA**

	0																				
Model		(4)		-	141			200	СОВ	3-xW48	80-11-2	4WI	, a	140					10.		-
Dimensions, mm										1000	x8x2.2										
Current, A										. ~(	0,5										
Voltage, V		100	100	1 0 1	141					- 24	DC		٠							100	
Power, W/m			-	•			•		٠	~	11	٠	•	٠		•	*	•		•	
LED quantity, pcs										4	80										
Color		100	-	100	N	eutral wh	ite						-		War	m w	hite		100	100	
Color temperature (CCT)		(40)	141	[4]	4	000K (-NV	V)	Sec.					-	. 6	3000	)K"(-\	ww	) "		141	7.0
Luminous flux, Lm			,			1300			٠			•		٠		1200					
Color rendering index (CRI)										>	90										
Light angle					100					18	80° -	-	140					100	100	100	
Working temperature (Tc point)		100	101		100	160				-25°-	+65°	-	-	*		100		700	1961	-	
Cutting step, mm					•					5	0										
Ingress protection										IP	65			-							
Package		Tark.	(40)		(4)					5 me	eters				141	w.	140	100	100	141	
	0-																				_