



SPECIFICATION

ITEM	SN-1000
OUTPUT POWER	CONTINUOUS POWER 1000W 1200W 10mini
SURGE POWER	2000W
STANDBY CURRENT	DC 12V < 1A DC 24V < 0.8A
GREEN POWER MODE	DC 12V < 0.1A DC 24V < 0.1A
INPUT VOLTAGE	DC12V : 10V~15V DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Pure Sine Wave
EFFICIENCY	> 85%
INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
TOTAL HARMONIC DISTORTION	< 3%
OUTPUT REGULATION	< ± 5% INTELLIGENT PWM
OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED.
COOLING	AUTO-OPERATION FAN
OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
LOW BATTERY	< 10.5V or 21.5V ± 0.5V PRE-ALARM < 10V or 20V ± 0.5V SHUT DOWN & ALARM
OVER HEATING	> 60°C PRE-ALARM > 65°C SHUT DOWN & ALARM
OVER LOAD	>1200W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 25A * 6PCS DC 24V : 20A * 6PCS
AC OUTLET	2 AC OUTLETS EUROPEAN TYPE : 1 AC OUTLET
DIMENSION (L*W*H)	360*195*80mm
NET WEIGHT	3.6Kg

ISO 9001:2008